



WATER-REPELLENT FOR POROUS SURFACES

Provides excellent water repellency, resists even on supports with high alkalinity and on surfaces both indoors and outdoors. Does not alter the natural colour of the material. The product penetrates and settles in the microporosities of the material causing the effect of water repellency, without affecting the breathability of the stone.



SOLVENT BASE



NATURAL EFFECT

TECHNICAL CHARACTERISTICS

Solvent based water repellent. Penetrates and settles in the microporosities giving lasting protection.

HOW TO APPLY IT

Tools



Applied by paintbrush, spraying with airless pump on the outside with a cloth or sponge.

Mode

Apply pure on completely dry and clean surfaces, using a paintbrush, cloth, sponge or spraying with an airless pump. For best results, repeat the operation after at least 15 minutes after the first application, applying wet on wet, making sure to evenly apply the amount that the material naturally absorbs. Avoid direct sunlight on the surface. If it is applied on little porous media in excess a sticky residue is created to be removed from the surface with a cloth or a clean sponge after a few seconds of application. Desired protection is reached 24 hours after treatment. After application, do not step on the surface, for 4-6 hours.

TECHNICAL DATA

Density at 25°C gr/ml	0.780
Appearance	opalescent liquid
Colour	transparent/opalescent



WHERE TO APPLY IT

- COTTO
- NATURAL STONES
- CEMENT
- GRANITE
- MARBLE



PLUS/ADVANTAGES

- DOES NOT CREATE SURFACE FILM
- PROTECTS THE MATERIAL FROM THE ABSORPTION OF WATER AND DIRT
- AVOIDS THE PRESENCE OF MOISTURE IN THE MATERIAL
- PREVENTS THE FORMATION OF MOULD, MOSS ETC
- UV RESISTANT AND PERSISTENT RAIN
- DOES NOT YELLOW OUTDOORS
- HAS BEEN TESTED WITH Q-SUN INSTRUMENTATION
- IT IS ANTI EFFLORESCENCE DOES NOT ALTER THE COLOR OF THE MATERIAL
- DOES NOT AFFECT THE BREATHABILITY OF THE MATERIAL



COVERAGE

The consumption depends greatly on the porosity of the material

1L of product

POROUS MATERIALS	20 m ² 215 sq.ft.
LOW ABSORBENT MATERIALS	40 m ² 430 sq.ft.

PACKAGING

0,25-1-5-10-20-200 litres.

HOW TO STORE IT

Under normal conditions of use and work, the product stored properly away from heat, moisture and direct sunlight is guaranteed 24 months. Close carefully the packaging after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances: If the surface is treated for the first time it is advisable to assess the effect and the adherence of the material on a sample or a hidden corner.

LEGISLATION

Before use please read the instructions on the safety data sheet and the following notes on the cans.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



Scans to
access
multimedia
contributions