



COLOR ENHANCER SEALER FOR QUARTZ SURFACES

Color enhancing protective treatment to be applied on quartz agglomerates for small and large surfaces. The product is odourless and easy to apply. Ideal for kitchen surfaces and all surfaces that can come into contact with food, since the product complies with 1935/2004 EC for food contact.


SOLVENT BASE

REVITALIZING

**APPROVED FOR
FOOD CONTACT**

TECHNICAL CHARACTERISTICS

Solvent-based, odourless product with low VOC emissions.

HOW TO APPLY IT

Tools



Brush, sponge or cloth, single brush.

Mode

The product must be applied on dry and clean materials. The presence of water, dust or dirty matter may influence the result regarding the uniformity of the surface. We suggest to spread the product by using a brush, a cloth or a sponge. Use the right quantity that the material naturally can absorb, help the absorption of the product with circular movements. Then, after 5-10 minutes from the application, rub the surfaces with a clean cloth doing circular movements to avoid the formation of glossy and sticky films. We suggest to repeat this treatment after at least one hour, in order to obtain the best protection. Do not stress the surface for 24-48 hours. In case of floor application, do not walk on the surface before 24 hours.

WHERE TO APPLY IT


AGGLOMERATE QUARTZ
glossy, honed or brushed


PLUS/ADVANTAGES


**APPROVED FOR FOOD
CONTACT**

**ENHANCES THE TONE AND
COLOUR AND THEREFORE
IT IS IDEAL TO RESTORE
THE PROTECTION**

**LOW VOC EMISSION
AND ODOURLESS**

**SUPERB ON VARIOUS FINISHES,
FROM GLOSSY TO ROUGH**

**LASTING ANTI-STAIN AND
WATER MARKS PROTECTION**

**RESISTANCE OVER TIME TO
DAILY AND EXTRAORDINARY
WASHING COMPLIES WITH UNI
EN 8298-14 REGULATION**

TECHNICAL DATA

Density at 25°C g/ml	0.99
Appearance	opalescent liquid
Standard colour	colourless

COVERAGE

1L of product	25-40 m ² 269-431 sq.ft.
----------------------	--

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



Scans to
access
multimedia
contributions

PACKAGING

1-5-10-200 litres.

HOW TO STORE IT

Under normal conditions of use and work, the product stored properly away from heat, moisture and direct sunlight is guaranteed 24 months. Close carefully the packaging after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances: If the surface is treated for the first time it is recommended to assess the effect and the adherence of the material on a sample or a hidden corner.

LEGISLATION

Before use please read the instructions on the safety data sheet and the following notes on the cans.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.