



STRONG ACID DESCALING DETERGENT

Concentrated detergent, suitable for the removal of dirt from the building site such as joint residues, rust, traces of wall paintings, mineral deposits and saltpetre, having marked detergent features it allows to obtain excellent results in the presence of greasy dirt.



WATER BASE



ACID


EXTRAORDINARY
MAINTENANCE

TECHNICAL CHARACTERISTICS

The product is scented and red coloured. Concentrated product to be diluted in water.

HOW TO APPLY IT

Tools



Can be applied using a wax spreader fleece.

Mode

Before starting work, it is advisable to protect anything that may be damaged by acid splashes. Remove coarse dirt from the surface that may be present. If the surface is very absorbent, it should be well moistened with water, before starting work. Apply the diluted product on the surface, using a single brush machine and proceed in strips; leave it on for at least 2-3 minutes, depending on the layer of dirt to be removed; After a maximum of 30 minutes, rinse with water. In case of very resistant dirt repeat the treatment in the same way. For small surfaces, it can also be applied with a sponge and paintbrush, instead of the cleaning machine (single brush or scrubber).

Cement*: the surface is very sensitive to acids, always work on surface saturated with water. Then depending on the porosity of cement and limestone layer to be removed, carefully consider the product concentration and contact time.

WHERE TO APPLY IT

- COTTO
- CLINKER
- PORCELAIN GRES
- CERAMIC TILES
- NATURAL STONES
acid resistant
- CEMENT*
see application modes



PLUS/ADVANTAGES

- ACTS QUICKLY AND EFFECTIVELY ON INORGANIC TENACIOUS DIRTY
- IT IS ALSO A PRODUCT OF EASY RINSING AND LEAVES NO RESIDUE
- GREAT FOR REMOVING RUST
- IDEAL FOR OUTDOOR

TECHNICAL DATA

Density at 25°C gr/cm ³	1.1
Appearance	clear liquid
Colour	red
pH 1.5, acid	

COVERAGE/DILUTION

Daily cleaning and descaling:
from 1:30 to 1:100 (10-30 g in 1 litre of water).

Thorough cleaning and descaling:
from 1:20 to 1:10 (50-100 g in 1 litre of water).

PACKAGING

0,75-5-10-20-200 litres.

HOW TO STORE IT

Under normal conditions of use and work, the product stored properly away from heat, moisture and direct sunlight is guaranteed 12 months. Close carefully the packaging after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances: If the surface is treated for the first time it is advisable to assess the effect and the adherence of the tile on a sample or a hidden corner.

LEGISLATION

Before use please read the instructions on the safety data sheet and the following notes on the cans.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



Scans to
access
multimedia
contributions