



UNI EN ISO 9001:2008  
Quality System Certified Company



TECHNICAL DATA SHEET  
PRODUCT

RISPLEND

**WASH-N-WAX for MARBLE, GRANITE,  
TERRACOTTA, CERAMIC TILES**

Water-based wash-n-wax based on modified acrylic polymers, waxes, polishing and sanitizing substances. Easy to apply and long lasting, RISPLEND is highly flexible and is suitable for the most different kind of materials. Once dry, shows a pleasant glossy and satiny effect. After drying, thanks to its special waxy components, when polished on reflecting surfaces is obtained a looking-glass polish.

<b>FUNCTION</b>	WATER-BASED WASH-N-WAX, WITH LIGHT ANTI-SKID EFFECT	
<b>LINE</b>	MAINTENANCE	HOUSE
<b>INDICATIONS</b>	For surfaces that have a light-medium soil level and that must be protected by a wax coating with glossy and satiny effect	
<b>MATERIALS</b>	All kind of surface (better if porous) such as MARBLE, GRANITE, TERRACOTTA, TERRAZZO, AGGLOMERATES, GRES PORCELAIN TILES etc.	
<b>HOW TO USE</b>	Under normal conditions, the product can be used in a 10 to 20% water dilution (for example, mix 1-2 part of RISPLEND to 10 parts water). RISPLEND can be used in any concentration depending on the degree of shine desired. Pass mop or cotton rag moistened with pure or diluted product over surfaces to be cleaned, scrubbing vigorously on heavily soiled areas. Do not rinse. Allow to dry before walking on surface. The dry surface can be polished with a buffing machine. To have best results a regular and periodical use is suggested.	
<b>TEST</b>	On a small surface effect always a preliminary test to determine consumption, the exact dilution, the drying time and, after drying, the aesthetic result	
<b>COMPOSITION</b>	Mixture of water, surfactants, soaps, waxes, coating substances and natural derivatives. Active ingredients over 20%.	
<b>TECHNICAL INFORMATION</b>	Consumption varies depending on the kind of surface or floor, dilution and the shine grade. The product <i>CANNOT STAND THE FROST</i> . Do not store an temperature lower than 5°C (41°F) or higher than 35°C (95°F).	
<b>NOTES</b>	The synergic combination of waxes and surfactants allows the easy removal of dirt while the surface maintains a thin protective coating that shines and adheres. After drying, buffing will intensify the shine of the protective wax coating. Clean and shine in a single application; no need to rinse.	
<b>IMPORTANT</b>	After drying, buffing may be done either manually or with a buffing machine fitted with a soft felt pad. This product respects the environment, is ecologically sound and leaves a pleasant eucalyptus aroma; primarily for use in private and public buildings such as restaurants, hotels and other common areas.	

**LIMITATION OF LIABILITY** The data provided derive from published information or from our own laboratory tests. The information provided here must be considered as a guideline and not as any form of performance guarantee. Since the application of the product is beyond the control of the manufacturer or supplier, our liability for defective products, when verified, is limited to refund of the purchase price

**A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION**