



PROFESSIONAL LINE



Honing & Polishing

FK 2

Water-based Crystallizer for Gloss Maintenance

FK 2 is a ready-to-use liquid crystallizer for marble or lime-based surfaces. **FK 2** restores the shine of the surfaces, without causing yellowing or greying, or even the pitted, "orange peel" effect.

BENEFITS	✓	Ready to use
	✓	Does not give the "orange peel" effect
	✓	Water-based product
	✓	Easy application

USES	Product suitable for indoor application
	Product suitable for application on: Marble, Travertine, Limestone

COVERAGE	50/70 m ² /kg
-----------------	--------------------------

APPLICATION EQUIPMENT	Single disc machine with at least 1.5 HP; steel-wool pad.
------------------------------	---

Faber Chimica can supply the WARRIOR single disc machine, which has a power of 2.2 HP and is optimized for the correct application of any product.

APPLICATION STEPS

Surface preparation

- Carefully clean the surface, making sure to remove any dust or dirt present. We suggest using **FABER 30**, depending on the nature of the dirt and the surface type.
- We suggest applying the product on surface sections of 1 m² at a time.
- Apply the product to surfaces with a temperature of between +5 and +40°C
- Any adjacent surfaces not being treated with the product must be protected.
- We suggest, before proceeding with the crystallization to pour **FK 2** into a bottle equipped with a wide spray nozzle. Doing so will significantly speed up the process.

Application

Before applying the product is necessary to take a preliminary test on an unexposed area or unused piece of material to check the product's suitability.

- Shake the bottle well and spray a small quantity of product directly onto the surface area you intend to crystallize. Generally, approximately 3-4 sprays of product are sufficient to crystallize 1 m² of surface.
- Immediately after dispensing, proceed to buff the product using a single disc machine equipped with steel wool pads for crystallization, with rpm between 150 and 200. Operate with the single-disc machine, paying attention to apply the product in circular motions evenly throughout the surface.
- Keep buffing the product until dry.
- Move to the following section applying the product as described above.
- Once the surface has been fully crystallized remove the residues from the steel-wool pad using a dry cloth or a vacuum cleaner.
- If the surface is particularly worn-out we recommend performing up to 3 applications per section.



PROFESSIONAL LINE



APPLICATION STEPS

- The product doesn't give layering defects so once the surface is fully crystallized there won't be differences of shine between sections.

Resuming the surface use

Resume surface use once the residues of the steel-wool pad have been removed.

MAINTENANCE PRODUCTS

- For the daily maintenance of a surface treated with **FK 2**, we recommend: **ALGAFLOOR** or **NEUGEL** depending on the type of material
- For heavy-duty cleaning of a surface treated with **FK 2**, we recommend **FABER 30**.

INSTRUCTIONS AND GUIDELINES

- Never apply the product to a wet surface
- Do not apply the product to overly heated surfaces
- Apply the product to surfaces with a temperature of between +5 and +40°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

PHYSICAL-TECHNICAL DATA

Formula	Liquid
Color	Pink
Odor	Unscented
pH:	2,5 ± 0,4
Specific weight at 20°C	1137 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

5 l Bottle – 4 bottles per box

SAFETY

When applying the product, always use suitable personal protective equipment and follow the product safety data sheet instructions with care.

Revisione 2.0 – 05/06/2024

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.