


Toner Black

ENHANCER FOR BLACK GRANITES

Sealing colour enhancer treatment specific for black granite. Its high toning performance and long life make it the ideal product for correcting defects typical of black granites and homogenising their colour.

Untreated



Treated



LONG-LASTING STRONG TONER



HOMOGENISES THE COLOUR



WATER-REPELLENT

Technical data:

- ◆ Density at 25°C gr/cm³: 840
- ◆ Standard colour: black
- ◆ Appearance: liquid

Indicative duration:

- ◆ Indoor: 12-24 months
- ◆ Outdoor: 6-12 months

The stated duration is merely indicative



Solvent based



Indoor
Outdoor

Tools:

- ◆ Brush
- ◆ Cloth
- ◆ Sponge
- ◆ Fleece



Natural stone

How to apply it:

- ◆ Apply the product to a dry, clean surface.
- ◆ Apply the product evenly.
- ◆ Do not expose to sunlight during application.
- ◆ If applied improperly, a sticky film will form.
- ◆ After a few minutes, wipe off excess product with a clean cloth.
- ◆ Do not step on the treated surface for 4-6 hours.
- ◆ After 24 hours, the treatment will be absorbed by the material, achieving the desired protection.

Indicative consumption 1 l:

Consumption depends on the porosity of the material - yield per coat

Granito e marmo lucido 30-40m²

Matt 20-30m²

Safety measures:

Read the instructions in the technical and safety data sheet and the notes on the packaging before use. Close the container after use. For professional use only.

Warnings:

When a surface is treated for the first time, it is advisable to evaluate the effect or adhesion on a sample or hidden corner.



Opening the can



Dampen the cloth



Product application



Excess removal



Protective effect



Final result