

Anti-Efflorescence

WATER-BASED ANTI-RISING DAMP PRE-LAYING TREATMENT

Pre-laying anti-rising damp treatment. It prevents the rising of ferrous salts and pollutants from the substrate towards the surface of the material, thus preventing the formation of stains and streaks without creating a surface film. Compatible with all laying products.



 PREVENTS RISING FERROUS SALTS AND POLLUTANTS

 COMPATIBLE WITH LAYING PRODUCTS

 PREVENTS THE FORMATION OF STREAKS AND STAINS

Technical data:

- ◆ Density at 25°C gr/cm3: 1,032
- ◆ Standard colour: colourless
- ◆ Appearance: clear liquid

Indicative duration:

- ◆ Indoor: permanent
- ◆ Outdoor: permanent

The stated duration is approximate



Water based



Indoor
Outdoor

Tools:

- ◆ Brush
- ◆ Cloth
- ◆ Sponge
- ◆ Fleece



Natural stone



Quartz

How to apply it:

- ◆ Apply the product to a dry, clean surface.
- ◆ Apply the product evenly.
- ◆ Do not expose to sunlight during application.
- ◆ If applied improperly, a sticky film will form.
- ◆ After a few minutes, wipe off excess product with a clean cloth.
- ◆ Repeat if necessary.
- ◆ Do not step on the treated surface for 4-6 hours.
- ◆ After 24 hours, the treatment will be absorbed by the material, achieving the desired protection.

Indicative consumption 1 l:

Consumption depends on the porosity of the material - yield per coat

Lava stone and marble	30-40m ²
Quartz	20-30m ²

Safety measures:

Read the instructions in the technical and safety data sheet and the notes on the packaging before use. Close the container after use. For professional use only.

Warnings:

When a surface is treated for the first time, it is advisable to evaluate the effect or adhesion on a sample or hidden corner.



Dampen cloth and/or sponge



Apply the product to the back of the material to be laid



Leave on



Final result