



DESCALING DETERGENT FOR QUARTZ SURFACES

Suitable for removing dirt and lime deposits from surfaces in quartz agglomerate.



WATER BASE



ACID



EXTRAORDINARY MAINTENANCE

TECHNICAL CHARACTERISTICS

Acid cleaner based on organic acids effective in removing stains and limescale deposits. Concentrated product to be diluted in water. Does not contain hydrochloric acid.

HOW TO APPLY IT

Tools



Applied by paintbrush, with a cloth or sponge.

Mode

Remove coarse dirt from the surface that may be present. Apply the diluted product on the surface, using a paintbrush or a sponge; leave on for a variable period (at least 2-3 minutes) depending on the layer of dirt to be removed; After a maximum of 30 minutes, rinse with water. In case of very resistant dirt repeat the treatment in the same way. For large surfaces, use a cleaning machine (single brush or scrubber).

STAINS AND DILUTION	CONTACT TIMES
Dirt and scale deposits, efflorescences, saltpetre:	
Use pure	2'
Ordinary cleaning scale, dilution from pure to 1:4	2'
Extraordinary cleaning scale, dilution from pure to 1:2	from 3' to 30'
Cement residues, Rust:	
Use pure	2'
dilution from pure to 1:3	from 5' to 30'
Food and fruit sugar residues:	
Ordinary cleaning, dilution from pure to 1:2	3'

WHERE TO APPLY IT

QUARTZ AGGLOMERATE
glossy, honed, brushed




PLUS/ADVANTAGES

- EFFECTIVE AND QUICK FOR EXTRAORDINARY CLEANING OPERATIONS
- VERY GOOD EVEN IN THE PRESENCE OF ORGANIC DIRT
- REMOVES LIMESCALE DEPOSITS
- EFFECTIVENESS AND RESPECT OF THE MATERIAL ACCORDING TO THE TESTS PERFORMED (UNI EN 8298-14)

TECHNICAL DATA

Density at 25 °C gr/ml	1,220
Appearance	liquid
Colour	light pink
Smell	scented



COVERAGE/DILUTION

Light dirt:
dilution from 1:100 to 1:30 (10/30 g in 1 litre of water)

Intermediate dirt:
dilution from 1:30 to 1:15 (30/60 g in 1 litre of water)

After checking on a small portion of the surface, the product can be applied pure


Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAXO cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAXO will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAXO is not responsible for incorrect use of the product.



Scans to access multimedia contributions

MADE in ITALY

AT YOUR DISPOSAL
TENAX.IT



PACKAGING

1-5-10-20-200 litres.

HOW TO STORE IT

Under normal conditions of use and work, the product stored properly away from heat, moisture and direct sunlight is guaranteed 12 months. Close carefully the packaging after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. If the surface is treated for the first time it is advisable to assess the effect and the sealing of the material on a sample or a hidden corner. do not use in conjunction with detergents that contain bleach. Do not use on marble and other acid-sensitive surfaces, it may cause corrosion and irreversible opacity. With a test, determine the sealing of the material, the duration of the application and the optimum concentration to obtain the required result.

LEGISLATION

Before use please read the instructions on the safety data sheet and the following notes on the cans.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.